

McKinney TA2714

Five Knuckle Standard Weight Hinge



SPECIFICATIONS:

MATERIAL:

Steel

DESCRIPTION:

Five Knuckle Standard
Weight Hinge

FASTENERS:

- (8) 1/2" x 12-24 Machine Screws
- (8) 1 1/4" x #12 Wood Screws

OPTIONS:

- NRP–Non-Removable Pin
- TB–Ball Bearing
- TCA–Concealed Bearing
- RC–Round Corner - 1/4" radius furnished unless specified
- HT–Hospital Tip
- BT–Ball Tip
- FT–Flat Decorative Tip
- GT–Grooved Tip
- LT–Lined Tip
- RT–Round Tip
- ST–Steeple Tip
- SSF–Safety Stud Feature
- CC–4, 8, or 12 wire available
- CC-18–2, 4, 6, 8, or 10 wire available (2-18AWG wires and the remainder 28AWG wires)
- QC–4, 8, or 12 wire available
- MM–Magnetic Monitoring

NOTES:

- When doors are beveled specify TA4714

SIZE:

4 1/2" x 4 1/2"

AVAILABLE FINISHES:

- P–Prime Coat
- US3/632
- US4/633
- US5/609
- US9/637
- US10/639
- US10A/641
- US10B/640
- US15/646
- US26/651
- US26D/652
- D3–Dark Bronze Powder Coat
- 10BE–Bronze Satin Powder Coat
- BSP–Black Suede Powder Coat
- WSP–White Suede Powder Coat

PACKAGED/WEIGHT:

- 3 ea Per Box
- 48 ea Per Case
- Case Weight–55 lbs

UL/ANSI:

NFPA 80 UL Openings
A8112 Grade 2