

Rockwood 2842

Automatic Flush Bolt Set

Experience a safer
and more open world



SPECIFICATIONS:

MATERIAL:

Brass, Stainless Steel

NOTE: There are ferrous and non-ferrous components within the material composition of the product.

FASTENERS:

20 ea. #8 x $3/4$ " Flat Head Combo Screws, 2 ea. #6-8 Plastic Anchors

FEATURES:

- For metal doors
- Non-handed
- Fully automatic-opening active door retracts top and bottom bolts
- Low closing force
- Override feature prevents damage to doors or bolts if bolt heads are blocked from entering strikes.
- Bolt head rods are adjustable up to $1\frac{1}{2}$ "
- Thermal lock automatically locks the inactive door under high heat conditions due to fire.
- For Fire Rated Hollow Metal Doors measuring up to 4'w x 8'h up to and including 3 hours.
- UL Listed

AVAILABLE FINISHES:

- US3/605
- US4/606
- US10/612
- 10BE/613E
- US26/625
- US26D/626
- US32D/630
- BSP (Black Suede Power Coat)
- WSP (White Suede Powder Coat)
- BPC (Black Powder Coat)
- WPC (White Powder Coat)
- FBPC (Flat Black Powder Coat)
- RPC (Red Powder Coat)

Size: 1" x $6\frac{3}{4}$ "

Weight: 2.4 lbs.

Rockwood Manufacturing Company
300 Main St.
Rockwood, PA 15557
www.rockwoodmfg.com
1800 458 2424

Copyright © 2019–2025, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited. Printed in the U.S.A.