

# Rockwood 2845

## Combination Flush Bolt Set

Experience a safer  
and more open world



NOTE: UL for metal door application

### SPECIFICATIONS:

#### MATERIAL:

Brass, Stainless Steel

NOTE: There are ferrous and non-ferrous components within the material composition of the product.

#### FASTENERS:

18 ea. #8 x 3/4" Flat Head  
Combo Screws; 2 ea. #6-8  
Plastic Anchors

#### FEATURES:

##### Top Bolt:

- Automatically engages when the inactive door closes. When the active door is opened, the inactive door stays latched at the top until the top bolt is released by pressing the plunger button on the bolt face.

##### Bottom Bolt:

- Non-handed
- Low closing force
- Fully automatic-opening active door retracts bottom bolt.
- Override feature prevents damage to door or bolt if bolt head is blocked from entering strike.
- Bolt head rod is adjustable up to 3/4".
- Thermal lock automatically locks the inactive door under high heat conditions due to fire.
- For Fire Rated Hollow Metal Doors measuring up to 4'w x 8'h rated up to and including 3 hours.

### AVAILABLE FINISHES:

- US3/605
- US4/606
- US10/612
- 10BE/613E
- US26/625
- US26D/626
- US32D/630
- BSP (Black Suede Powder Coat)
- WSP (White Suede Powder Coat)
- BPC (Black Powder Coat)
- FBPC (Flat Black Powder Coat)
- RPC (Red Powder Coat)

Size: 1" x 6 3/4"

Weight: 2.4 lbs.