

# Rockwood 2942

## Automatic Flush Bolt Set

Experience a safer  
and more open world



**OPTION:**  
Can be used with the  
No. 570 Dust Proof Strike

### SPECIFICATIONS:

#### MATERIAL:

Brass, Stainless Steel

NOTE: There are ferrous and non-ferrous components within the material composition of the product.

#### FASTENERS:

12 ea. #8 x 3/4" Flat Head Combo Screws; 4 ea. #8-32 x 1/2" Flat Head Machine Screws; 6 ea. #10 x 1" Flat Head Wood Screws; 2 ea. #6-8 Plastic Anchors

#### FEATURES:

- For wood doors
- Non-handed
- Fully automatic-opening active door retracts top and bottom bolts.
- Low closing force
- Override feature prevents damage to doors or bolts if bolt heads are blocked from entering strikes.
- Wood door flush bolts cannot be extended in size. Extension rods are not available to change the overall size of the product.
- Bolt head rods are adjustable up to 3/8".
- Thermal lock automatically locks the inactive door under high heat conditions due to fire
- For Fire Rated Composite Wood doors up to 4'w and 8'h up to and including 90 minutes.
- UL Listed

### AVAILABLE FINISHES:

- US3/605
- US4/606
- US10/612
- 10BE/613E
- US26/625
- US26D/626
- US32D/630
- BSP (Black Suede Powder Coat)
- WSP (White Suede Powder Coat)
- BPC (Black Powder Coat)
- WPC (White Powder Coat)
- FBPC (Flat Black Powder Coat)
- RPC (Red Powder Coat)

**Size:** 1" x 8 1/2"

**Weight:** 2.9 lbs.

Rockwood Manufacturing Company  
300 Main St.  
Rockwood, PA 15557  
[www.rockwoodmfg.com](http://www.rockwoodmfg.com)  
1800 458 2424

Copyright © 2019–2025, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited. Printed in the U.S.A.