

# Rockwood 2945

## Combination Flush Bolt Set

Experience a safer  
and more open world



### SPECIFICATIONS:

#### MATERIAL:

Brass, Stainless Steel

NOTE: There are ferrous and non-ferrous components within the material composition of the product.

#### FEATURES:

- For wood doors
- Can be used with the No. 570 Dust Proof Strike
- UL Listed

#### Top Bolt:

- Automatically engages when the inactive door closes. When the active door is opened, the inactive door stays latched at the top until the top bolt is released by pressing the plunger button on the bolt face.

#### Bottom Bolt:

- Non-handed
- Low closing force
- Fully automatic-opening active door retracts bottom bolt.
- Override feature prevents damage to door or bolt if bolt head is blocked from entering strike.
- Wood door flush bolts cannot be extended in size. Extension rods are not available to change the overall size of the product.
- Bolt head rod is adjustable up to  $\frac{3}{8}$ ".
- Thermal lock automatically locks the inactive door under high heat conditions due to fire.
- For Fire Rated Wood Composite Doors up to 4'w x 8'h rated up to and including 90 minutes.

#### FASTENERS:

10 ea. #8 x  $\frac{3}{4}$ " Flat Head Combo Screws; 4 ea. #8-32 x  $\frac{1}{2}$ " Flat Head Machine Screws; 6 ea. #10 x 1" Flat Head Wood Screws; 2 ea. #6-8 Plastic Anchors

### AVAILABLE FINISHES:

- US3/605
- US4/606
- US10/612
- 10BE/613E
- US26/625
- US26D/626
- US32D/630
- BSP (Black Suede Powder Coat)
- WSP (White Suede Powder Coat)
- FBPC (Flat Black Powder Coat)
- RPC (Red Powder Coat)

Size: 1" x 8  $\frac{1}{2}$ "

Weight: 2.9 lbs.

Rockwood Manufacturing Company  
300 Main St.  
Rockwood, PA 15557  
[www.rockwoodmfg.com](http://www.rockwoodmfg.com)  
1800 458 2424

Copyright © 2019–2025, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited. Printed in the U.S.A.