

# Rockwood 550

## Lever Extension Flush Bolt

Experience a safer  
and more open world



### SPECIFICATIONS:

#### MATERIAL:

Brass

NOTE: There are ferrous and non-ferrous components within the material composition of the product.

#### FASTENERS:

8 ea. #8 x 3/4" Flat Head  
Combo Screws

#### FEATURES:

- For Fire Rated Hollow Metal Swinging Doors measuring up to 4'w x 10'h rated up to and including 3 Hours
- 3/4" bolt throw, 3/4" rod backset
- 12" rod length (center of face to bolt end - retracted)
- 1 1/2" adjustable bolt head

#### OPTIONS:

- Other size rods available are 18", 24", 36", 48"
- Use #570 Dust Proof Strike to prevent dirt blocking bottom strike

NOTE: UL Rated for use on Metal Doors only.

### AVAILABLE FINISHES:

- US3/605
- US4/606
- US10/612
- US10B/613
- 10BE/613E
- US26/625
- US26D/626
- BSP (Black Suede Power Coat)
- WSP (White Suede Powder Coat)
- BPC (Black Powder Coat)
- WPC (White Powder Coat)
- FBPC (Flat Black Powder Coat)
- RPC (Red Powder Coat)

#### Size:

Face Plate: 1 1/4" x 6 3/4"

Strike: 15/16" x 2 1/4"

Guide: 1" x 2"

Weight: 1.7 lbs./2

### ⚠️ WARNING

This product can expose you to lead which is known to the state of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65warnings.ca.gov](http://www.P65warnings.ca.gov).

Rockwood Manufacturing Company  
300 Main St.  
Rockwood, PA 15557  
[www.rockwoodmfg.com](http://www.rockwoodmfg.com)  
1800 458 2424