

Rockwood 556WS

Windstorm Flush Bolt



⚠️ WARNING

This product can expose you to lead which is known to the state of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65warnings.ca.gov.

SPECIFICATIONS:

MATERIAL:

Brass, Stainless Steel

NOTE: There are ferrous and non-ferrous components within the material composition of the product.

FEATURES:

- 3/4" Bolt Throw, 3/4" Rod Backset
- 12" Stainless Steel Rod Length (Center of Face to Bolt End- Retracted)
- 1 1/2" Adjustable Bolt Head

STANDARDS:

- Meets ANSI A156.16, L04251
- UL Certified
- Assembly Approved for Use in the State of Florida, Including the High Velocity Hurricane Zone (HVHZ)
- Fire Rated up to and Including 3 Hours on hollow metal doors up to 4'wide and 10'high.

FASTENERS:

8 ea. #8-32 x 1/4" Flat Head Machine Screws in Stainless Steel

AVAILABLE FINISHES:

- US26D/626

Size:

Face Plate: 1" x 6 3/4" x 1/8"

Rod: 12" x Ø 1/2"

Mortise Body: 1" x 5 1/4" x 1 3/8"

Strike: 15/16" x 2 1/4"

Guide: 1" x 2"

Weight: 2.5 lbs./2

Rockwood Manufacturing Company
300 Main St.
Rockwood, PA 15557
www.rockwoodmfg.com
1800 458 2424

Copyright © 2019–2025, ASSA ABLOY Accessories and Door Controls Group, Inc. All rights reserved. Reproduction in whole or in part without the express written permission of ASSA ABLOY Accessories and Door Controls Group, Inc. is prohibited. Printed in the U.S.A.