

ACCENTRA®

ASSA ABLOY

Experience a safer
and more open world

YPL SERIES

Cylindrical Indicator Lock



TABLE OF CONTENTS

Contents

Features, Applications, Specifications	3
How to Order, Finishes	4
Lever Trim	5
Function	6
Indicator Options	6
Latchbolts	7
Strikes	7
Technical Specifications and Listings	8

Increased Privacy

The cylindrical lock indicator visually displays door status; whether the door is locked or unlocked, thus eliminating potentially embarrassing situations and providing a peace of mind.

Using a standard bored lock door prep, this indicator lock is ideal for new construction or retrofit applications.

WARNING

This product can expose you to lead which is known to the state of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65warnings.ca.gov.

FEATURES, APPLICATIONS, SPECIFICATIONS

Features

- Red or Green window display with padlock icon for visual door status
- Cylindrical lock construction for durability and longevity in high use applications
- Patented design
- Privacy function (F76A) with push button lock and for automatic unlock when inside lever is pushed down
- One motion for egress
- Coin turn or emergency key/tool for emergency access
- Through-bolted for robust operation
- Ideal for retrofit

Applications

- Office buildings
- Restaurants
- Schools
- Hospitals
- Warehouses
- Airports
- Places of Worship
- Convenience Stores
- Gas Stations
- Travel Centers



Specifications

Door Prep	ANSI/SDI A250.14
Door Thickness	1-3/4" (44mm) standard, accommodates 1-3/8" (35mm) with adapter plate kit (ordered separately, specify APK-2)
Backset	2-3/4" (70mm) standard, 2-3/8" (60mm) optional
Handing	Non-handed
Latchbolt	Plain, 2-3/4" (70mm) backset x 1-1/8" (29mm) square corner front with 1/2" (13mm) throw standard, 2-3/8" (60mm) x 1" (25mm) optional
Strike	ANSI strike 4-7/8" x 1-1/4" x 1-1/4" (124mm x 32mm x 32mm) lip to center
ANSI/BHMA	2-3/4" Backset: Certified Grade 1, ANSI/BHMA A156.2, Series 4000 2-3/8" Backset: Certified Grade 2, ANSI/BHMA A156.2, Series 4000
UL/cUL	Listed for 3 hour fire doors
Warranty	3 years



HOW TO ORDER, FINISHES

Trim Design	Function	Hand	Latch	Strike	Door Thickness	Finish
AU - Augusta PB - Pacific Beach TB	YPL02 - Privacy, Bedroom or Bath YPL42 - Privacy, Bedroom or Bath	RH standard; units are non-handed.	693A standard; see page 7 for options.	497 standard; see page 7 for options.	1-3/4" Use spacer plates for 1-3/8"; see page 8	605 613E 626 BSP

Ordering Example

Trim Design	Function	Hand	Latch	Strike	Door Thickness	Finish
TB	YPL42	RH	693A	497	1-3/4"	626

Finishes


ANSI/BHMA Code Finish Description			
605 Bright Brass, Clear Coated	613E Dark Oxidized Satin Bronze - equivalent	626 Satin Chrome Plated	BSP Black Suede Powder Coat
			

TRIM DESIGNS

Augusta AU

Lever: Cast Zinc


Rose: Wrought Brass



Pacific Beach PB

Lever: Cast Zinc


Rose: Wrought Brass



TB



Lever: Cast Zinc

Rose: Wrought Brass




AU and PB levers comply with codes requiring lever to return to within 1/2" (13mm) of door face.
Dimensions shown are in inches/mm.

FUNCTIONS

YPL02 (F76A)	YPL42 (F76A)
Privacy Lock with Indicator (Coin Turn Override) • Either lever operates latchbolt unless outside lever is locked by pushbutton inside. • Pushbutton inside changes indicator display status outside. • Rotating inside lever and/or closing door unlocks outside lever and changes indicator display status outside. • Coin turn in outside lever for emergency access. • Inside lever always active. • Outside lever rigid when in locked position.  Outside Inside	Privacy Lock with Indicator (EM Key/Tool Override) • Either lever operates latchbolt unless outside lever is locked by pushbutton inside. • Pushbutton inside changes indicator display status outside. • Rotating inside lever and/or closing door unlocks outside lever and changes indicator display status outside. • Emergency key/tool (provided) inserted and turned in outside lever will unlock door from outside. • Inside lever always active. • Outside lever rigid when in locked position.  Outside Inside

Indicator Display

YPL Series locks are provided standard with a visual display that shows red with a closed shackle padlock for locked and green with an open shackle padlock for unlocked. The padlock icons are positioned in a manner that allows for the locks to be non-handed.




Other options may be available by special application, contact Customer Service for more information.

LATCHBOLTS

Model No. 693A supplied standard with all YPL locksets. Standard latchbolt has a 2-1/4" (57mm) x 1-1/8" (29mm) beveled square front with a 2-3/4" (70mm) backset and a 1/2" (13mm) throw bolt. Optional 2-3/8" latchbolt available to order.

Model	Front	Backset	Throw	"W" Front Width	Latch Diameter
693A	Square	2-3/4" (70mm)	1/2" (13mm)	1-1/8" (29mm)	1" (25mm)
378PL	Square	2-3/8" (60mm)	1/2" (13mm)	1" (25mm)	7/8" (22mm)*

*1/8" sleeve supplied to accommodate 1" preps.



STRIKES

Model No. 497 ANSI Strike (Standard)	Model No. 371 T-Strike	Model No. 70S Full Lip	Model No. 202 Strike Box
For door and frames with ANSI/SDI A250.14 preparations 4-7/8" x 1-1/4" x 1-1/4" (124mm x 32mm) lip to center supplied standard. Other lip lengths available by special order. Available with optional 202 Strike Box. Specify 497 x 202.	2-3/4" x 1-1/8" x 1-1/4" (70mm x 29mm x 32mm) lip to center supplied standard. Other lip lengths available by special order. Wrought strike box supplied.	2-1/4" x 1-3/4" x 1-1/4" (57mm x 44mm x 32mm) lip to center with full lip anti-rattle tab.	Available to special order. Specify x 202.

TECHNICAL SPECIFICATIONS AND LISTINGS

ADA

The YPL Series meets accessibility guidelines of the Americans with Disabilities Act and the requirements of the Uniform Federal Accessibility Standards and ANSI 117.1, all requiring ease of accessibility for the handicapped.



ANSI/BHMA

2-3/4" Backset: Certified ANSI/BHMA A156.2, Series 4000 Grade 1.

2-3/8" Backset: Certified ANSI/BHMA A156.2, Series 4000 Grade 2.



Fire Listings




UL/cUL Listed for up to 3 hours

Note: Any retrofit or other field modification to a fire rated opening can potentially impact the fire rating of the opening, and ASSA ABLOY ACCENTRA® makes no representations or warranties concerning what such impact may be in any specific situation. When retrofitting any portion of an existing fire rated opening, or specifying and installing a new fire-rated opening, please consult with a code specialist or local code official (Authority Having Jurisdiction) to ensure compliance with all applicable codes and ratings.

Door Thickness

The YPL Series installs on 1-3/4" thick doors standard. It can also be used on 1-3/8" thick doors by adding adapter plates. To order specify adapter plate kit model number APK-2.



APK-2

Installation


YPL Series Cylindrical locks conform to ANSI/SDI A250.14 hardware preparations for steel doors and steel frames.

Warranty

The YPL Series cylindrical lever locks carry a three-year warranty.

Emergency Key Tool

Provided standard with YPL42 function for emergency access when locked. To order separately, specify part number 14-4602-1002-048.



The ASSA ABLOY Group is the global leader in access solutions.
Every day, we help billions of people experience a more open world.

ASSA ABLOY Opening Solutions leads the development within door openings and products for access solutions in homes, businesses and institutions. Our offering includes doors, frames, door and window hardware, mechanical and smart locks, access control and service.

ACCENTRA®
ASSA ABLOY

TECHNICAL SUPPORT

(troubleshooting, product use and application, returns)

Tel: 855-557-5078

Email: techsupport.accentra@assaabloy.com

CUSTOMER SUPPORT

(orders, product configuration, pricing, lead-time)

Tel: 855-557-5078 x2

Email: Customerservice.Accentra@assaabloy.com

U.S.A.:

ASSA ABLOY ACCENTRA®

225 Episcopal Road
Berlin, CT 06037-4004

Tel: 1-800-438-1951

Fax: 1-800-338-0965

www.accentra-assaabloy.com

Canada:

ASSA ABLOY Door Security Solutions Canada

160 Four Valley Drive
Vaughan, Ontario L4K 4T9

Tel: 1-800-461-3007

Fax: 1-800-461-8989

assaabloydss.ca

International:

ASSA ABLOY Americas International

Tel: 1-905-821-7775

Fax: 1-905-821-1429

assaabloyai.com